



501.42899X00  
S.N. 10/610,683

## SUBSTITUTE SPECIFICATION

### TITLE OF THE INVENTION

### DISPLAY DEVICE

### BACKGROUND OF THE INVENTION

#### 1. ~~Field of the Invention:~~

5 {0001}

The present invention relates to a display device of the type which utilizes an emission of electrons into a vacuum space, which is defined between a face front substrate and a back substrate, and, more particularly, the invention relates to a display device in which can arrange there are arranged, with high accuracy, cathode lines having electron sources and control electrodes, which control a the quantity of electrons ~~led or emitted~~ from the electron sources, and which display device can exhibit stable display characteristics by ~~holding~~ maintaining a vacuum between the front substrate and the back substrate.

{0002}

#### 15 2. ~~Description of the Related Art~~

As a display device which exhibits ~~the a~~ high brightness and ~~the~~ high definition, color cathode ray tubes have been widely used conventionally. However, along with the recent request for ~~the~~ higher quality in the generation of images ~~of in~~ information processing equipment or television broadcasting, ~~the~~ there has been an increased demand for planar displays (panel displays), which are light in weight and require a small space, while exhibiting ~~the a~~ high brightness and ~~the a~~ high definition ~~has been increasing~~.

[0003]

As typical examples, liquid crystal display devices, plasma display devices and the like have been ~~put into practice~~ commercialized. Further, ~~particularly,~~ as display devices which can realize ~~the~~ a higher brightness, it is expected that various kinds of panel-type display devices, including a display device which utilizes ~~an~~ the emission of electrons from electron Sources into a vacuum (hereinafter, referred to as "an electron emission type display device" or "a field emission type display device"), and an organic EL display device, which is characterized by low power consumption, will be commercialized.

10 [0004]

Among such panel type display devices, ~~as the above-mentioned~~ there are various types of field emission type display ~~device~~ devices, including a display device having an electron emission structure ~~which was invented as developed~~ by C. A. Spindt et al, a display device having an electron emission structure of a metal-insulator metal (MIM) type, a display device having an electron emission structure which utilizes an electron emission phenomenon based on a quantum theory tunneling effect (also referred to as a "surface conduction type electron source"), and a display device which utilizes an electron emission phenomenon observed with a diamond film, a graphite film and carbon nanotubes and the like ~~have been known~~.

20

[0005]

The field emission type display device includes a back substrate, on which ~~forms~~ cathode lines having electron-emission-type electron sources and control ~~electrode~~ electrodes are formed on an inner surface thereof, and a front substrate, on which ~~forms~~ an anode and a fluorescent material are formed on an inner

25

surface which faces the back substrate, wherein, both substrates are laminated to each other by inserting a sealing frame between the inner peripheries of both substrates, and the inside ~~thereof~~ space between substrates is evacuated.

Further, to set a distance between the back substrate and the front substrate to a given value, distance holding members are provided between the back substrate and the front substrate.

[0006]

The distance holding members for ~~holding~~ maintaining the distance between the back substrate and front substrate are formed of ~~a thin plate~~ plates made of glass or ceramics, ~~and which~~ are provided ~~disposed~~ in an ~~erected~~ erect manner at positions ~~away~~ spaced from the pixels. Here, as conventional examples of ~~the a~~ display device provided with such distance holding members, attention is directed to Japanese Unexamined Patent Publication 326306/1995 and Japanese Unexamined Patent Publication 338528/2001 ~~can be named~~.

## 15 SUMMARY OF THE INVENTION

[0007]

Fig. 1(a) and Fig. 1(b) are schematic ~~explanatory views of~~ showing the overall constitution of a field emission type display device, wherein Fig. 1(a) is a plan view as viewed from a front substrate side, and Fig. 1(b) is a side view, which is obtained by viewing Fig. 1(a) in the direction of ~~an~~ the arrow A therein. In Fig. 1(a) and Fig. 1(b), numeral 1 indicates a back substrate, numeral 2 indicates a front substrate, numeral 3 indicates an outer frame and numeral 4 indicates an exhaust pipe (in a sealed state). At the back substrate 1, on an insulating substrate which is preferably made of glass or ceramics, such as alumina, a plurality of cathode lines having electron sources extend in ~~one a~~ first direction (x

direction) and are juxtaposed in ~~another~~ a second direction (y direction). Above these cathode lines, there are a plurality of control electrodes<sub>1</sub> which are insulated from the cathode lines, extend in the y direction and are juxtaposed in the x direction ~~are provided~~. Further, the outer frame 3 is interposed between the outer peripheries of the opposing back substrate 1 and front substrate 2 ~~which so as to~~ define the distance therebetween<sub>1</sub> and the inside space, which is surrounded by the outer frame 3<sub>1</sub> is evacuated and sealed in vacuum. The front substrate 2 is stacked on the back substrate 1 in the z direction. After laminating the back substrate 1 and the front substrate 2 ~~by~~ while interposing the outer frame 3 therebetween, the inside ~~of the outer frame 3~~ space between the substrates is evacuated using an exhaust pipe 4<sub>1</sub> and the inside ~~of the outer frame 3~~ space is sealed at a given degree of vacuum.

[0008]

Fig. 2(a) and Fig. 2(b) are schematic ~~explanatory views of a constitutional~~ diagrams showing an example of the back substrate<sub>1</sub> which constitutes a part of the display device shown in Fig. 1(a) and Fig. 1(b), wherein Fig. 2(a) is a plan view as ~~viewed~~ seen from an upper side in the z direction<sub>1</sub> and Fig. 2(b) is a side view which is obtained by viewing Fig. 2(a) in the direction of ~~an~~ the arrow B therein. Numeral S indicates cathode lines, numeral 6 indicates plate-member control electrodes, numeral 7 indicates electrode pressing members, and numeral 8 indicates an exhaust hole. In Fig. 2(a) and Fig. 2(b), numerals which are equal ~~to the same as~~ those in Fig. 1(a) and Fig. 1(b) indicate identical functional parts. Here, the exhaust pipe shown in Fig. 2(a) and Fig. 2(b) is shown in a state before sealing. The plate-member control electrodes 6 are configured by arranging a large number of strip-like electrode elements having electron passing apertures in

parallel. These plate-member control electrodes 6 ~~are~~ have been proposed by the inventors of the present invention in the course of developing the present invention and do not constitute the prior art.

{0009}

5           On an inner surface of the back substrate 1, cathode lines 5 are mounted. The cathode lines 5 extend in the x direction on the back substrate 1 and are juxtaposed in a large number in the y direction<sub>1</sub> which crosses the x direction. The cathode lines 5 are patterned by printing a conductive paste<sub>1</sub> including silver or the like. End portions of the cathode lines 5 are ~~pulled~~ extended outside the outer  
10   frame 3 as cathode line pullout lines Sa. On the cathode lines 5, electron sources<sub>1</sub> such as metal-insulator-metal (MIM) type electron emission elements, electron emission structure (also referred to as a surface conductive electron source) elements which make use of an electron emission phenomenon generated by a  
15   nanotubes or the like (not shown in the drawing)<sub>1</sub> are formed.

{0010}

          The plate-member control electrodes 6 shown in Fig. 2(a) and Fig. 2(b) are manufactured in a separate processing step as separate parts. Further, the plate-member control electrodes 6 are arranged above (front substrate side) and in the  
20   vicinity of the cathode lines 5 having electron sources<sub>1</sub> and they are fixed to the back substrate 1 using electrode pressing members 7<sub>1</sub> which are provided outside the display region and inside the outer frame 3 and are formed of an insulating body made of glass material or the like. Pullout lines are connected to the plate-member control electrodes 6 in the vicinity of the electrode pressing members 7<sub>1</sub>,  
25   or in the vicinity of the outer frame 3<sub>1</sub> and these pullout lines are ~~pulled~~ extended

out to an outer periphery of the display device (not shown in the drawing). Then

With this construction, pixels are formed in a matrix array on crossing portions

between cathode lines 5 and the plate-member control electrodes 6, and the

above-mentioned display region is formed on the pixels which are arranged in a

5 matrix array. Here, it is also possible to make the outer frame 3 have-perform the function of the electrode pressing member 7.

{0011}

Here, ~~an~~ the emission quantity (including ON/OFF states) of electrons from

the electron sources formed on the cathode lines 5 is controlled in response to the

10 potential difference generated between the cathode lines 5 and the plate-member

control electrodes 6. On the other hand, the front substrate 2 shown in Fig. 1(a)

and Fig. 1(b) is made of an insulating material having, optical transmissivity, such

as glass, wherein the front substrate 2 includes anodes and phosphors on an

inner surface thereof. The phosphors are formed at locations corresponding to the

15 pixels formed at the crossing portions of the cathode lines 5 and the plate-member

control electrodes 6. Further, a light shielding layer (black matrix) is provided

around the phosphors.

{0012}

Vacuum is created by evacuating air from the ~~inside of~~ space between the

20 front substrate 2 and the back substrate 1, which is sealed by the outer frame 3,

~~from through~~ the exhaust hole 8 ~~through via~~ the exhaust pipe 4, so that the degree

of vacuum of  $10^{-2}$  to  $10^{-5}$  Pa, for example, is obtained. Electron passing apertures

(not shown in the drawing) are formed in each crossing portion of the plate-

member control electrode 6 and the cathode line 5 so as to allow electrons

25 emitted from the electron source formed on the cathode line 5 to pass

therethrough toward the front substrate side (anode side). It is necessary to mount the plate-member control electrodes 6 on the back substrate 1 on which the cathode lines 5 are formed and over the whole display region with a given gap with respect to the cathode lines 5.

5 {0013}

The distance holding members are usually formed of a large number of thin glass plates or the like, ~~and~~ which are arranged vertically (z direction) between the plate-member control electrodes 6, such that they form partition walls between the back substrate and the front substrate. Accordingly, the assembling ~~step~~ of the distance holding members requires a delicate and sophisticated expertise.

Further, ~~a~~ the stress which ~~cooperates with a~~ accompanies the vacuum pressure is applied to the distance holding members from the front substrate and the back substrate; and, hence, unless a plurality of the distance holding members are arranged to receive the stress uniformly, ~~the~~ a stress concentration occurs on some distance holding members, thus giving rise to ~~the~~ a rupture of the distance holding members per se, the front substrate or the back substrate.

{0014}

~~In the invention disclosed in the~~ The above-mentioned Japanese Unexamined Patent Publication 326306/1995, which provides one of the countermeasures to cope with such a drawback, proposed the use of a material which is obtained by applying a paste, having silver as a main component, as a resilient material between distance holding members and a substrate and baking the paste, or an inorganic adhesive having a low Young's modulus ("ARON Ceramics", a product of Toa Gosei Kagaku Ltd. in the embodiment) is used.

Further, in the above-mentioned Japanese Unexamined Patent Publication

338528/2001, this as an arrangement in which conductive frits are interposed between the distance holding members and the substrates. However, the Young's modulus which these materials possess as ~~the~~ a resilient material is not considerably large (flexible) compared to that of possessed by the glass plate or the ceramics plate which constitutes the distance holding members ~~possesses~~, and, hence, ~~a~~ the stress dispersion effect is limited. ~~Particularly~~ In addition, when a conductive paste is used on the back substrate on which cathode lines and control electrodes are formed, there arises a problem with respect to the insulating property.

10 {0015}

Further, mounting of the distance holding members requires the arrangement of the distance holding members between the back substrate and the front substrate with high accuracy and with uniformity; and, at the same time, it is necessary to ~~make~~ ensure that the stress attributed to atmospheric pressure is uniformly applied to a large number of distance holding members. However, in the above-mentioned ~~prior art~~ conventional schemes, only ~~a viewpoint~~ the consideration that the distance holding members ~~are~~ should be mounted in an ~~erected~~ erect manner between the back substrate and the front substrate is taken into account. That is, the ~~prior art does~~ conventional methods do not taken take account of the mounting of the distance holding members in ~~the~~ a display device in which ~~arranges~~ control electrodes are arranged between the back substrate and the front substrate.

20 {0016}

Accordingly, it is an object of the present invention to mount a large number of distance holding members with high accuracy in a display device in which



arranges-control electrodes are arranged between a back substrate and a front substrate.

Further, it is another object of the present invention to provide a highly reliable display device, ~~by making a~~ in which it is ensured that stress attributed to atmospheric pressure is substantially uniformly applied to a large number of distance holding members, so as to suppress ~~the~~ rupture of the distance holding members, the back substrate or the front substrate.

[0017]

To achieve the above-mentioned objects, in accordance with the present invention, with respect to a large number of distance holding members, which are arranged in an ~~erected-erect~~ manner between a back substrate and a front substrate ~~and so as to hold a~~ and maintain the distance between both substrates, buffering/fixing materials are interposed at portions thereof which are brought into contact with the above-mentioned back substrate and/or front substrate, which buffering/fixing materials ~~which have a~~ high resiliency sufficient to substantially uniformly disperse ~~an-the~~ atmospheric pressure applied thereto from the back substrate and the front substrate, and each of which is constituted of a buffer material and an adhesive ~~are interposed, and the~~ . These distance holding members are fixed between the back substrate and the front substrate ~~due to~~ by the application of heat treatment and pressurizing steps.

[0018]

Due to such a constitution of the present invention, the buffer material is fixed such that ~~the~~ pressure is applied to many distance holding members in the above-mentioned heat treatment and pressurizing steps. As a result, it is possible to suppress ~~the~~ a rupture of the distance holding members, the back substrate or

the front substrate. ~~To explain the~~ Examples of typical constitutions of the present invention, ~~they~~ are as follows.

[0019]

(1) A display device comprises:

5 a front substrate ~~forming on which~~ anodes and phosphors are formed on an inner surface thereof;

a back substrate on which forms there are a plurality of cathode lines, which extend in ~~one~~ a first direction and are juxtaposed in ~~another~~ a second direction, which crosses the ~~one~~ first direction, and have electron sources, and a  
10 plurality of control electrodes, which cross the cathode lines in a non-contact manner within a display region, extend in the above-mentioned ~~another~~ second direction, are juxtaposed in the above-mentioned ~~one~~ first direction, and have electron passing apertures which allow electrons from the electron sources to pass therethrough ~~on an inner surface thereof~~, the back substrate being arranged  
15 to face the front substrate in an opposed manner with a given distance therebetween; and

distance holding members being sandwiched between the front substrate and the back substrate in an ~~erected~~ erect manner ~~and holding a~~ to hold the distance between the front substrate and the back substrate to a given distance;  
20 wherein

a buffering/fixing material is provided between at least one of the front substrate and the back substrate and the distance holding members, and the buffering/fixing material is formed by mixing an adhesive ~~to~~ with a highly resilient material, which has high resiliency at the time of assembling and dissipates in a  
25 baking step.

[0020]

(2) In the above-mentioned constitution (1), the control electrodes are constituted of plate-members<sub>1</sub> which are formed by arranging a plurality of strip-like electrode elements in parallel.

5 (3) In the above-mentioned constitution (2), the display device includes an outer frame<sub>1</sub> which is interposed between the front substrate and the back substrate<sub>1</sub> such that the outer frame surrounds the display region so as to hold maintain the given distance, and

the display device further includes electrode pressing members<sub>1</sub> which fix  
10 both end regions of the strip-like electrode elements which constitute the control electrodes<sub>1</sub> to the back substrate<sub>1</sub> outside the display region and ~~the~~ inside the outer frame.

[0021]

(4) In the above-mentioned constitutions (1) to (3), a low-temperature  
15 decomposing foamed resin is used as the above-mentioned highly resilient material.

[0022]

(5) In the above-mentioned constitution (4), urethane is used as the above-mentioned low-temperature decomposing foamed resin.

20 (6) In any one of the above-mentioned constitutions (1) to (5), a low melting-point glass is used as the adhesive.

[0023]

(7) A display device comprises:

a front substrate ~~forming on which~~ anodes and phosphors are formed on an  
25 inner surface thereof;

a back substrate on which forms there are a plurality of cathode lines,  
which extend in ~~one~~ a first direction and are juxtaposed in ~~another~~ a second  
direction, which crosses the ~~one~~ first direction, and has electron sources, and a  
plurality of control electrodes, which cross the cathode lines in a non-contact  
5 manner within a display region, extend in the above-mentioned ~~another~~ second  
direction, are juxtaposed in the above-mentioned ~~one~~ first direction, and have  
electron passing apertures which allow electrons from the electron sources to  
pass therethrough ~~on an inner surface thereof~~, the back substrate being arranged  
to face the front substrate in an opposed manner with a given distance  
10 therebetween; and

distance holding members being sandwiched between the front substrate  
and the back substrate in an ~~erected~~ erect manner ~~and holding a~~ to hold the  
distance between the front substrate and the back substrate to a given distance;  
wherein

15 a buffering/fixing material is provided between at least one of the front  
substrate and the back substrate and the distance holding members, and the  
buffering/fixing material is formed by mixing an adhesive ~~to~~ with a highly resilient  
material, which has high resiliency and is present as a reinforcing material after a  
baking step.

20 [0024]

(8) In the above-mentioned constitution (7), the control electrodes are  
constituted of plate members which are formed by arranging a plurality of strip-like  
electrode elements in parallel.

(9) In the above-mentioned constitution (8), the display device includes  
25 an outer frame which is interposed between the front substrate and the back

substrate<sub>1</sub> such that the outer frame surrounds the display region, so as to hold  
maintain the given distance, and

the display device further includes electrode pressing members<sub>1</sub> which fix  
both end regions of the strip-like electrode elements which constitute the control  
5 electrodes<sub>1</sub> to the back substrate<sub>1</sub> outside the display region and inside the outer  
frame.

{0025}

(10) In the above-mentioned constitutions (7) to (9), heat-resistant fibers  
are used as the above-mentioned highly resilient material.

10 {0026}

(11) In the above-mentioned constitution (10), aramid-based fibers are  
used as the heat-resistant fibers.

{0027}

(12) In any one of the above-mentioned constitutions (7) to (11), a low  
15 melting-point glass is used as the adhesive.

{0028}

Due to the above-mentioned respective constitutions, the atmospheric  
pressure which is applied to a large number of distance holding members which  
are arranged between the back substrate and the front substrate in an erected  
20 manner becomes substantially uniform so that it is possible to obviate the rupture  
of the back substrate, the front substrate or the distance holding members. Here,  
as the highly resilient material, besides the materials described above, a plastic  
material formed of foamed polyethylene or acetate fibers can be used.

#### BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1(a) is a plan view and, Fig. 1(b) ~~are schematic explanatory views~~ is a side view as seen in the direction of arrow A in Fig. 1(a), showing the overall constitution of a field emission type display device.

Fig. 2(a) is a plan view and, Fig. 2(b) ~~are schematic explanatory views~~ is a side view as seen in the direction of arrow B in Fig. 2(a), showing a constitutional  
5 an example of a back substrate, which constitutes the display device shown in Fig. 1(a) and Fig. 1(b).

Fig. 3(a) is a plan view and, Fig. 3(b) ~~are explanatory views~~ is a side view as seen in the direction of arrow C in Fig. 3(a), showing a first embodiment of the  
10 display device according to the present invention.

Fig. 4 is an enlarged view of ~~a D~~ the portion of D in Fig. 3(b).

Fig. 5 is a ~~schematic explanatory view of~~ diagram showing an assembling jig of  
for use in mounting the distance holding members.

Fig. 6 is a cross-sectional view taken along a line D-D' in Fig. 5.

Fig. 7(a), Fig. 7(b) and Fig. 7(c) are ~~schematic explanatory views of~~  
15 diagrams showing examples of a the shape of a slit formed in the assembling jig shown in Fig. 5.

Fig. 8 is a ~~schematic view~~ diagram showing a state in which the distance holding member is aligned with the slit shown in Fig. 7(a) ~~in place.~~

Fig. 9(a) is a plan view, and Fig. 9(b) and Fig. 9(c) are ~~schematic side~~  
20 views for explaining as seen in the direction of arrows E and F, respectively, in Fig. 9(a), showing the constitution of the back substrate to which the distance holding members are fixed.

Fig. 10(a) ~~is a plan view,~~ and Fig. 10(b) ~~are schematic explanatory views of~~  
a ~~constitutional~~ is a section taken along line G-G' in Fig. 10(a), showing an  
example of the front substrate in the first embodiment of the present invention.

Fig. 11 is a cross-sectional view of an ~~essential~~ part of the display device in  
5 which the front substrate is assembled and integrally formed with the back  
substrate.

Fig. 12 is an enlarged view of an ~~H~~ the portion H in Fig. 11.

Fig. 13(a) ~~is a plan view and,~~ Fig. 13(b) ~~are explanatory views of is a~~  
section taken along line I-I' in Fig. 13(a), showing a third embodiment of the  
10 display device according to the present invention.

Fig. 14 is a ~~detailed explanatory cross-sectional~~ view showing the back  
substrate and the structure for mounting the distance holding members in an  
~~erected erect~~ manner, as shown in Fig. 13(a) and Fig. 13(b).

Fig. 15 is an enlarged view of a ~~the portion indicated by K~~ in Fig. 14.

## 15 DESCRIPTION OF THE PREFERRED EMBODIMENTS

[0029]

Preferred embodiments of the present invention ~~are~~ will be explained in  
detail hereinafter in conjunction with the drawings ~~which show these~~  
embodiments.

20 [0030]

(Embodiment 1)

Fig. 3(a) and Fig. 3(b) ~~are explanatory views of~~ show a first embodiment of  
a display device according to the present invention. Fig. 3(a) and Fig. 3(b) ~~are~~  
~~served for schematically explaining~~ illustrate the mounting structure of distance  
25 holding members, wherein Fig. 3(a) is a plan view of an ~~essential~~ part of a back

substrate in a state ~~that a~~ in which the front substrate is removed, and Fig. 3(b) is a side view of the mounting structure as viewed in the direction of ~~an~~ the arrow C in Fig. 3(a). In these drawings, numeral 9 indicates distance holding members, and the other numerals used in Fig. 3(a) and Fig. 3(b), which are ~~equal to the~~ same as numerals used in Fig. 2, indicate identical functional parts. The distance holding members 9 are arranged between adjacent plate-member control electrodes 6.

{0031}

Further, Fig. 4 is an enlarged view of ~~a~~ the portion D in Fig. 3(b). In Fig. 4, numeral 10 indicates a buffering/fixing material, which is formed by mixing urethane resin, serving as low-temperature decomposing foamed resin having high resiliency, ~~to~~ with a low melting glass, serving as an adhesive. The urethane resin has a property ~~to dissipate~~ in which it dissipates at a temperature of about 350°C. The buffering/fixing material 10 is applied onto the cathode lines 5 formed on the back substrate 1 and along and between the plate-member control electrodes 6. On the buffering/fixing material 10, one ~~ends~~ end of the distance holding members 9 ~~are erected~~ is mounted, using a jig similar to a jig which will be described later. In this embodiment, the buffering/fixing material 10 is arranged at intervals of every three plate-like member control electrodes 6 corresponding to three unit pixels. These three unit pixels correspond to R, G, B colors which constitute ~~4~~ one trio pixel of a color display. However, the positions where distance holding members 9 are mounted are not limited to the above-described positions.

{0032}



Although not shown in the drawing, ~~another ends~~ the other end of the distance holding members 9 are brought into contact with the front substrate.

Although the ~~another ends~~ other end of the distance holding members 9 may be fixed using only an adhesive, such as frit glass or the like, it is needless to say that  
5 a similar buffering/fixing material 10 can be interposed between the distance holding members 9 and the front substrate.

{0033}

Since the distance holding members 9 are joined to the back substrate 1 by way of the buffering/fixing material 10 in a state ~~that in which~~ the buffering/fixing  
10 material 10 is applied to the back substrate 10-side, ~~different from~~ as opposed to a case in which only an adhesive is directly applied to the distance holding members 9, ~~an applying the~~ quantity of the buffering/fixing material 10 being applied can be made uniform. Accordingly, a large number of distance holding members 9 can be temporarily mounted in an ~~erected~~ erect manner on the back  
15 substrate by way of the buffering/fixing material 10, which is applied in a substantially equal quantity and over a-substantially the whole surface thereof. The buffering/fixing material 10 may be baked temporarily in this state.

{0034}

Fig. 5 is ~~a schematic explanatory view of~~ shows an assembling jig which is  
20 used for mounting the distance holding members. Further, Fig. 6 is a cross-sectional view taken along a line D-D' in Fig. 5. In Fig. 5 and Fig. 6, numeral 11 indicates a lower-side jig member, numeral 11a indicates projections, numeral 12 indicates an-uppers upper-side jig member, and numeral 12a indicates stepped portions. Numerals which are ~~equal to~~ the same as those in the previously-  
25 mentioned drawings indicate identical functional parts. In Fig. 5 and Fig. 6, the

~~detailed constitution details~~ of the back substrate 1 ~~is~~ are omitted. A plate-member control electrode master plate 60 may be formed of plate-member control electrodes of an actual device, ~~the~~. The plate-member control electrode master plate 60 is manufactured using a photo mask, which is also used for manufacturing the plate-member control electrodes 6.

[0035]

Fig. 7(a), Fig. 7(b) and Fig. 7(c) are ~~schematic explanatory views~~ diagrams showing examples of a the shape of a slit formed in the assembling jig shown in Fig. 5, while Fig. 8 is a ~~schematic view~~ diagram showing the state in which the distance holding member is aligned with the slit shown in Fig. 7(a) ~~in place~~. In the lower-side jig member 11, which constitutes a part of the assembling jig of the present invention, slits 11b ~~which are formed at given intervals to~~ enable the easy insertion of the thin distance holding members 9; and, for this purpose, they have upper portions thereof which are widened to ~~provide~~ receive these members 9 and lower portions to facilitate the vertical ~~arrangement~~ disposition of the distance holding members 9 ~~are formed at a given interval~~. The slit 11b has a planar shape as shown in Fig. 7(a), Fig. 7(b) or Fig. 7(c). That is, the slit 11b has a wide opening portion 11b' at ~~an~~ one end portion thereof. In inserting the distance holding member 9 into the slit 11b formed in the lower-side jig member 11, as shown in Fig. 8, a corner of the distance holding member 9 is ~~firstly~~ first aligned with and is inserted into the wide opening portion 11b'; and, subsequently, the whole distance holding member 9 is rotated down and inserted into the slit 11b, as indicated by ~~an~~ the arrow.

[0036]

By providing such a slit shape, it is possible to easily insert the distance holding member 9 into the slit lib formed in the lower-side jig member 11. Here, the position where the wide opening portion 11b' is formed in the slit 11b is not limited to the end portion of the slit 11b as shown in Fig. 7(a), Fig. 7(b) and Fig. 7(c), and the wide opening portion 11b' also may be formed in a proper intermediate portion of the slit 11b.

[0037]

Returning to Fig. 5 and Fig. 6, the plate-member control electrode master plate 60 is mounted on projections ha of the lower-side jig member 11, and the ~~upper~~ upper-side jig member 12, ~~having which has~~ a stepped portion 12a, is mounted on the plate-member control electrode master plate 60 so as to hold the plate-member control electrode master plate 60. The plate-member control electrode master plate 60 has a ~~the~~ periphery thereof fixed by a frame body. A large number of gaps 60a, which correspond to an interval between strip-like electrode elements of an actual display device, are formed in the plate-member control electrode master plate 60. The gaps 60a and the slits 11b formed in the lower-side jig member 11 are aligned with each other in the z direction. The back substrate 1, to which the distance holding members 9 are temporarily fixed, is mounted on the stepped portions 12a of the upper-side jig member 12.

Alternatively, it is possible to align and overlap the back substrate 1 on the stepped portions 12a of the upper-side jig member 12 after arranging the distance holding members described below.

[0038]

Here, the distance holding members 9 are inserted into the slits 11b formed in the lower-side jig 11 ~~in~~ using the mode-procedure explained in conjunction with

Fig. 8 by allowing the distance holding members 9 to pass through the gaps 60a formed in the plate-member control electrode master plate 60. Further, with respect to the gaps 60a formed in the plate-member control electrode master plate 60, by slightly widening an the gap on the insertion side, of the distance holding member 9 as seen in Fig. 6, the insertion of the distance holding member 9 is facilitated.

[0039]

A The length of a the distal end portion of the distance holding member 9 which is projected into the slit 11b formed in the lower-side jig 11 from the gap 60a formed in the plate-member control electrode master plate 60 is preferably set to 1/4 to 1/3 of the height of the distance holding member 9 to take the operability into consideration. In this type of field emission type display device, electrons are emitted with the intensity of an electric field of  $3\text{V}/\mu\text{m}$ ; and, hence, provided that a distance of about 3mm is ensured between the plate-member control electrode 6 and the anode formed on the front substrate, it is possible to apply a high voltage of about 10kV. Accordingly, the above-mentioned projection quantity is set to a value slightly less than 1mm.

[0040]

The back substrate 1 is set to into the jig as shown in Fig. 6 and is subjected to a heat treatment while pressure is applied to the whole surface from above the back substrate 1. In this pressuring and heating treatment, due to a buffer action of urethane resin possessed by the buffering/fixing material 10, the pressure is uniformly applied to a plurality of the distance holding members 9; and, thereafter, the distance holding members 9 are fixed to the back substrate 1 due to melting and solidifying of the frit glass contained in the buffering/fixing

material 10. Simultaneously, the urethane resin is dissipated. Since the frit glass starts softening ~~thereof~~ at a temperature in the vicinity of 350°C, when the urethane resin is decomposed and loses ~~the~~its resiliency, the paste-like frit glass plays ~~a~~the role of a cushion material between the distance holding members 9 and the back substrate 1. Further, after performing the ~~heating~~heat treatment at 450°C for about 30 minutes, the temperature is lowered so as to solidify the frit glass. Thereafter, the back substrate 1, to which one ends of the distance holding members 9 are fixed, is removed from the jig.

[0041]

Fig. 9(a), Fig. 9(b) and Fig. 9(c) ~~are schematic views for explaining the constitution of~~show the back substrate to which the distance holding members are fixed, wherein Fig. 9(a) is a plan view of the distance holding member, Fig. 9(b) is a side view as ~~viewed~~seen from the direction of ~~an~~the arrow B in Fig. 9(a), and Fig. 9(c) is a side view as viewed from the direction of ~~an~~the arrow F in Fig. 9(a). Although the buffering/fixing material 10 has a thickness of about 1mm before baking, in a state after solidifying, as shown in Fig. 9(a), Fig. 9(b) and Fig. 9(c), the thickness becomes about 0.1mm. In applying the buffering/fixing material 10 to the back substrate 1 side and mounting and fixing the distance holding members 9 on the back substrate 1, it is desirable to make ~~an~~the area of application ~~area~~ of the buffering/fixing material 10 broader than ~~a~~the cross section of the distance holding member 9.

[0042]

Fig. 10(a) and Fig. 10(b) ~~are schematic explanatory views showing a constitutional~~show an example of the front substrate of the first embodiment of the present invention. Fig. 10(a) is a plan view, and Fig. 10(b) is a cross-sectional

view taken along a line G-G' in Fig. 10(a). Further, Fig. 11 is a cross-sectional view of ~~an essential~~ part of a display device in which a front substrate is integrally incorporated into a back substrate, and Fig. 12 is an enlarged view of ~~an H~~ a portion H in Fig. 11. In Fig. 11 and Fig. 12, numeral 2 indicates the front substrate, numeral 13 indicates anodes, numeral 14 indicates phosphors and numeral 15 indicates a light shielding film (black matrix). The phosphors 14 constitute ~~4-one~~ one trio pixel with ~~an a color~~ a color arrangement of red (R), green (G), and blue (B).

~~Respective~~ The respective colors are defined or partitioned by the black matrix 15.

In this embodiment, a buffering/fixing material 10 for mounting distance holding

members 9 is applied for every 4-trio pixel (R, G, B).

[0043]

For example, ~~4-one~~ one trio pixel (R, G, B) of the phosphors 14 formed on the front substrate 2 is about 1mm, and a gap of about 0.1mm may be provided between the phosphors (phosphor elements) of respective colors. Assuming that the distance holding member 9, having a thickness of about 50 $\mu$ m, is mounted in the gap, to ensure the tolerance of 10 to 15 $\mu$ m for preventing the complete removal of the distance holding member 9 from an application region of the buffering/fixing material 10, it is desirable to set an application width of the buffering/fixing material 10 to 70 to 80 $\mu$ m. Further, it is desirable to set an application length of the buffering/fixing material 10 to about a length of the distance holding member 9 + 10mm, provided that the alignment tolerance between the buffering/fixing material 10 and the distance holding member 9 is, ~~respectably~~ respectively, 5mm at both ends.

[0044]

The front substrate 2<sub>1</sub> shown in Fig. 10(a), is laminated to the back substrate 1<sub>1</sub> to which the distance holding members 9 shown in Fig. 9 are fixed by way of an outer frame. The outer frame 3, the back substrate and the front substrate 2 are adhered to each other using an adhesive 3a<sub>1</sub> such as frit glass.

5 Here, ~~another~~ other ends of the distance holding members 9<sub>1</sub> provided to the back substrate 1 shown in Fig. 9<sub>1</sub> are aligned with the buffering/fixing material 10 that is applied to the front substrate 2 side shown in Fig. 10. The average particle size of the phosphors formed on the front substrate 2 is about 2 to 5μm<sub>1</sub> and ~~a~~ the film thickness of the phosphors is about 10μm. The anode 13<sub>1</sub> which is formed on the  
10 front substrate 2 so as to cover the front substrate 2<sub>1</sub> is formed of, for example, a thin aluminum film (so-called metal back). ~~A~~ The film thickness of the anode 13 is about 70nm to 100nm when the anode voltage is about 10kV.

[0045]

Fig. 11 is a schematic cross-sectional view showing ~~an essential~~ part of the  
15 display device formed by laminating the back substrate 1 and the front substrate 2 by way of the outer frame 3. Further, Fig. 12 is an enlarged view of a portion H in Fig. 11. One ~~ends~~ end of the distance holding members 9 ~~are~~ is mounted in an ~~erected~~ erect manner on the cathode lines 5 by way of the buffering/fixing material 10 that is disposed between the neighboring plate-member control electrodes 6  
20 formed on the back substrate 1, while ~~another ends~~ the other end of the distance holding members 9 ~~are~~ is held by the buffering/fixing material 10 provided to the anode 13 at positions of the black matrix 15 which are arranged between the phosphors 14 formed on the front substrate 2. In this constitutional example, ~~the a~~  
distance holding member 9 is mounted for every set of 4 one trio color pixel (R, G,  
25 B). The mounting number of distance holding members 9 is calculated based on

the strength of the distance holding members 9. For example, when glass having a width of about 100 $\mu$ m is used, the distance holding members 9 may be arranged at an interval of 35mm; while, when glass having a width of about 50 $\mu$ m is used, the distance holding members 9 may be arranged at an interval of 16mm.

5 {0046}

Heating is performed in this state, while pressurizing the back substrate 1 and the front substrate 2 in opposing directions; and, thereafter, the temperature is lowered so as to make the buffering/fixing material 10 fix the distance holding members 9, such that a uniform stress is applied between both substrates 1, 2.

10 Thereafter, a display device is completed through a discharging step and an aging step. According to this embodiment, a large number of the distance holding members 9 can be mounted with high accuracy in the display device, in which ~~arranges the~~ plate-member control electrodes 6 are arranged between the back substrate 1 and the front substrate 2. Further, the stress attributed to the  
15 atmospheric pressure is uniformly applied to a large number of the distance holding members 9; and, hence, ~~the~~ rupture of the distance holding members 9, the back substrate 1 or the front substrate 2 can be suppressed, whereby it is possible to obtain a highly reliable display device.

{0047}

20 (Embodiment 2)

In the above-mentioned first embodiment, as the buffering/fixing material 10, ~~the a~~ material which is prepared by mixing ~~the an~~ adhesive ~~to the~~ with a highly resilient material made of foamed resin, such as urethane resin, which possesses high resiliency during assembling and dissipates in the baking process, is used. A

25 The second embodiment of the present invention is characterized in that, in place



of the foamed resin which dissipates in the baking step, a buffering/fixing material which is prepared by mixing an adhesive ~~to~~with a resilient material made of a heat-resistant aramid-based resin fibers or the like<sub>1</sub> which do not dissipate by heating at a high temperature in a short time<sub>1</sub> is used.

5 {0048}

When the fibers made of heat-resistant aramid-based resin (product name: Kevlar or the like) ~~is~~are used as the resilient material, a sheet made of aramid-based resin fibers is placed between the distance holding members 9 and the back substrate 1 and/or the front substrate 2<sub>1</sub> and an adhesive<sub>1</sub> such as frit glass<sub>1</sub> having a low melting point<sub>1</sub> is applied to a periphery and an upper portion thereof. Alternatively, a sheet made of aramid-based resin fibers<sub>1</sub> in which the adhesive is impregnated<sub>1</sub> is inserted between the distance holding members 9 and the back substrate 1 and/or the front substrate 2. Ensuing pressurizing and heat treatment are performed in the same manner as the previous embodiment. Due to the heat treatment, the aramid-based resin fibers remain at fixing portions as a reinforcing material.

{0049}

Also<sub>1</sub> according to this embodiment, a large number of the distance holding members 9 can be mounted with high accuracy in the display device,in which ~~arranges the plate-member control electrodes 6~~ are arranged between the back substrate 1 and the front substrate 2. Further, the stress attributed to the atmospheric pressure is uniformly applied to a large number of the distance holding members 9<sub>1</sub> and<sub>1</sub> hence, ~~the~~ rupture of the distance holding members 9, the back substrate 1 or the front substrate 2 can be suppressed, thereby it is possible to obtain a highly reliable display device.

[0050]

(Embodiment 3)

Fig. 13 (a) and Fig. 13 (b) ~~are explanatory views of~~ show a third embodiment of the display device according to the present invention. That is, Fig.

5 13 (a) and Fig. 13 (b) schematically ~~explain~~ show the mounting structure of the distance holding members 9, wherein Fig. 13 (a) is a plan view of ~~an essential part~~ of a back substrate<sub>1</sub> shown in a state ~~that a~~ in which the front substrate is removed<sub>1</sub> and Fig. 13 (b) is a cross-sectional view taken along a line I-I' in Fig. 13(a). Further, Fig. 14 ~~is a detailed explanatory view of the~~ shows a structure in  
10 which distance holding members 9 are mounted on the back substrate 1 in an ~~erected~~ erect manner, as shown in Fig. 13 (a) and Fig. 13 (b). Fig. 15 is an enlarged view of ~~a the~~ the portion ~~indicated by~~ K in Fig. 14.

[0051]

In the drawings, numeral 6d indicates electron passing apertures. ~~Further,~~  
15 and the other numerals which are ~~equal to the same as~~ those in the above-mentioned embodiments indicate identical functional parts. In this embodiment, the distance holding members 9 traverse the plate-member control electrodes 6 and are mounted at positions corresponding to the spaces between cathode lines 5. By mounting the distance holding members 9 such that the distance holding  
20 members 9 traverse the plate-member control electrodes 6, an interval between respective strip-like electrode elements which constitute the plate-member control electrodes 6 can be firmly ~~held~~ maintained, and<sub>1</sub> hence, the displacement of the position of the plate-member control electrode 6 and the occurrence of deformation<sub>1</sub> such as twisting<sub>1</sub> can be suppressed. In this embodiment, in the  
25 same manner as the first embodiment, as the buffering/fixing material 10, a

material which is prepared by mixing an adhesive ~~to~~with a highly resilient material made of foamed resin<sub>1</sub> such as urethane resin<sub>1</sub> which exhibits a high resiliency during assembling and dissipates in a baking step<sub>1</sub> is used.

{0052}

5 Further, as shown in Fig. 14 and Fig. 15, it is desirable to adopt the following constitution. That is, a portion of the plate-member control electrode 6 which comes into contact with the distance holding member 9 is arranged between neighboring electron passing apertures 6d (one or a plural number) formed in the plate-member control electrode 6 for every pixel<sub>1</sub> and it is arranged  
10 at a position where the plate-member control electrode 6 comes into contact with the back substrate 1<sub>1</sub> directly or by way of an insulation layer, whereby the plate-member control electrode 6 can be firmly pushed.

{0053}

In the plate-member control electrode 6 used in the display device of this  
15 embodiment, a recessed portion 6a is formed at a portion where the plate-member control electrode 6 crosses the cathode line 5, ~~while so that~~ the plate-member control electrode 6 comes into contact with ~~a projection~~projections 6b<sub>1</sub> which ~~constitutes~~are formed by the above-mentioned recessed ~~portion~~portions 6a. Further, a cut-out portion 6c is formed in the plate-member control electrode 6  
20 ~~in an~~on the opposite side (front substrate side)<sub>1</sub> which corresponds to the location of the projection 6b<sub>1</sub> and one end of the distance holding member 9 is mounted in the cut-out portion 6d. It is preferable that<sub>1</sub> by imparting a taper which opens upwardly to an inner wall of the cut-out portion 6c, when ~~the~~ pressure is applied to the distance holding member 9 from above, the position of the one end of the  
25 distance holding member 9 can be corrected by the taper. Further, the adhesive

or the buffering/fixing material 10 which is applied to the front substrate 2 in this embodiment is provided on the black matrix 15 in the x direction in Fig 10.

{0054}

Then, the front substrate 2 is laminated to the back substrate 1, and the  
5 pressure is applied uniformly from both substrate sides so as to ~~make-cause~~ the  
pressure applied to the distance holding members 9 ~~uniformly to be uniform~~. The  
distance holding members 9 are fixed to the back substrate 1 by frit glass, which  
is melted and solidified in an ensuing baking step. Here, the urethane resin  
dissipates in this baking step. In this manner, it is possible to mount the distance  
10 holding members 9 such that the stress is uniformly applied between the back  
substrate 1 and the front substrate 2 with respect to the applied pressure.

{0055}

Other constitutions and advantageous effects of this embodiment are  
substantially ~~equal to~~ the same as those of the above-mentioned embodiments.  
15 Also, according to this embodiment, a large number of the distance holding  
members 9 can be mounted with high accuracy in the display device, in which  
~~arranges the plate-member control electrodes 6~~ are arranged between the back  
substrate 1 and the front substrate 2. Further, the stress attributed to the  
atmospheric pressure is uniformly applied to a large number of the distance  
20 holding members 9; and, hence, ~~the~~ rupture of the distance holding members 9,  
the back substrate 2 or the front substrate 1 can be suppressed, whereby it is  
possible to obtain a highly reliable display device.

{0056}

(Embodiment 4)

In the above-mentioned third embodiment, as the buffering/fixing material 10, ~~the a~~ material which is prepared by mixing ~~the a~~ adhesive ~~to the~~ with a highly resilient material made of foamed resin<sub>1</sub> such as a urethane resin<sub>1</sub> which possesses high resiliency during assembling and dissipates in the baking process<sub>1</sub> is used. A fourth embodiment of the present invention is characterized in that<sub>1</sub> in place of the foamed resin which dissipates in the baking step, a buffering/fixing material<sub>1</sub> which is prepared by mixing an adhesive ~~to~~ with a resilient material made of a heat-resistant aramid-based resin fibers or the like<sub>1</sub> which do not dissipate by heating at a high temperature for a short time and remains as a reinforcing material<sub>1</sub> is used.

{0057}

When the fibers made of heat-resistant aramid-based resin (product name: Kevlar or the like) ~~is~~ are used as the resilient material, a sheet made of aramid-based resin fibers is placed between the distance holding members 9 and the back substrate 1 and/or the front substrate 2<sub>1</sub> and an adhesive<sub>1</sub> such as frit glass<sub>1</sub> having a low melting point<sub>1</sub> is applied to a periphery and an upper portion thereof. Alternatively, a sheet made of aramid-based resin fibers<sub>1</sub> in which the adhesive is impregnated<sub>1</sub> is inserted between the distance holding members 9 and the back substrate 1 and/or the front substrate 2. Ensuing pressurizing and heat treatment are performed in the same manner as the previous embodiments. After the heat treatment, the aramid-based resin fibers remain as a reinforcing material.

{0058}

Also<sub>1</sub> according to this embodiment, a large number of the distance holding members 9 can be mounted with high accuracy in ~~the a~~ display device in which ~~arranges the plate-member control electrodes 6~~ are arranged between the back

substrate land the front substrate 2. Further, the stress attributed to the atmospheric pressure is uniformly applied to a large number of the distance holding members 9<sub>1</sub> and<sub>1</sub> hence, the-rupture of the distance holding members 9, the back substrate 2 or the front substrate 1 can be suppressed, whereby it is possible to obtain a highly reliable display device.

{0059}

Further, in the above-mentioned second and fourth embodiments, in place of applying the ~~an~~ adhesive such as frit glass after mounting the heat resistant resin fibers, it is also possible ~~that~~ to first apply the adhesive<sub>1</sub> such as frit glass<sub>1</sub> is firstly-applied-and, thereafter, mount the heat resistant resin fibers ~~are mounted~~. In this case, heating is performed until the adhesive<sub>1</sub> such as the frit glass<sub>1</sub> is softened<sub>1</sub> and, thereafter, pressurizing is performed.

{0060}

Further, in the above-mentioned respective embodiments, the explanation is mainly ~~made with respect~~ directed to cases in which the buffering/fixing material 10 is mounted on the back substrate 1 side and the front substrate 2 side. However, it may be possible to adopt ~~the constitution~~ a construction in which the buffering/fixing material 10 is provided to only one of both substrates<sub>1</sub> and only an adhesive is applied to ~~another~~ the other side.

{0061}

(Embodiment 5)

Since electrons emitted from the electron source of the cathode line 5 are not focused, when the buffering/fixing layer 10<sub>1</sub> or the adhesive layer at the front substrate 2 side having the phosphors<sub>1</sub> is constituted of a completely -insulated body, the electrons are charged in the buffering/fixing layer 10 or the adhesive

layer<sub>1</sub> thus giving rise to problems<sub>1</sub> such as image retention and lowering of contrast. To avoid the occurrence of such charging, ~~the~~a specific resistance of about  $10^{11}$  to  $10^{12}$   $\Omega\cdot\text{cm}$  may be imparted to the buffering/fixing layer 10 or the adhesive layer. In this embodiment, a trace amount of conductive particles<sub>1</sub> such as ATO<sub>1</sub> is mixed into the buffering/fixing layer 10 or the adhesive layer. Further, a filler which controls ~~a~~the resistance value may be mixed into the conductive material.

{0062}

As the material which controls the resistance value, it is possible to use a silica coat liquid<sub>1</sub> which is used for surface treatment of cathode ~~lay~~ray tubes or the like. By heating the silica coat at a high temperature, the silica coat is dealcoholized by a sol-gel reaction<sub>1</sub> thus forming polysiloxane coupling<sub>1</sub> and the above-mentioned conductive particles are caught in the polysiloxane coupling<sub>1</sub> whereby the silica coat can ~~obtain~~attain a stable conductivity. Accordingly, it is possible to realize ~~the~~a countermeasure against charging of the front substrate 2 to which a high voltage is applied. Further, by mixing a material having a light shielding property ~~to~~into the above-mentioned buffering/fixing layer 10 or the adhesive layer, it is possible to form the buffering/fixing layer 10 or the adhesive layer in ~~a~~the black matrix BM applying step.

20 {0063}

Here, as a material of the black matrix BM, a material which is softened at 400°C to 450°C may be used. Further, to impart ~~the~~a light shielding property to the black matrix EM, an oxide<sub>1</sub> such as chromium oxide ( $\text{Cr}_2\text{O}_3$ ), iron oxide ( $\text{Fe}_2\text{O}_3$ ) or the like<sub>1</sub> may be added to the black matrix BM. Accordingly, a step ~~for~~of forming the buffering/fixing layer 10 or the adhesive layer can be eliminated<sub>1</sub> so

that the number of manufacturing steps can be reduced and the manufacturing cost also can be ~~also~~ reduced.

[0064]

According to this embodiment, a large number of the distance holding members 9 can be mounted with higher accuracy in the display device in which ~~arranges the~~ plate-member control electrodes 6 are arranged between the back substrate 1 and the front substrate 2. Further, the stress attributed to the atmospheric pressure is uniformly applied to a large number of the distance holding members; and, hence, the rupture of the distance holding members 9, the back substrate 1 or the front substrate 2 can be suppressed, whereby it is possible to obtain a highly reliable display device.

[0065]

As has been explained heretofore, according to typical embodiments of the present invention, in ~~the a~~ display device in which ~~arranges the~~ distance holding members are arranged between the back substrate having the plate-member control electrodes constituted of a large number of the parallel strip-like electrode elements and the front substrate having the phosphors and the anode, the stress applied to the distance holding members can be made substantially uniform, and assembling of the distance holding members can be accurately performed, whereby it is possible to provide ~~the a~~ highly reliable display device ~~by obviating the in which~~ rupture of the distance holding members, the back substrate and. the front substrate is obviated.